



RIGXAN-L PLUS tm LIQUID XANTHAN VISCOSIFIER

Description

RigXan-L plus tm is liquid viscosifier slurry, containing high purity clarified Xanthan gum suspended in an environmentally acceptable synthetic base fluid.

Typical Physical Properties

Appearance	Tan Liquid
Odor	Mild Alcohol
Specific Gravity @ 60°F	1.12 – 1.132
Density (lbs /gallon)	9.6
Flash Point	>168°F
pH	5.5 – 7.5

Advantages

- Faster yielding than dry xanthan polymer, RigXan-L plus tm provides reliable rapid dispersion.
- Smooth, uniform solution viscosity with no lumping.
- No “fish eyes” or other dispersion problems are encountered due to the exceptional mixing characteristics of RigXan-L plus tm
- Compatible with most drilling muds and workover /completion fluids.
- No pack-down, settling, or separation - remains pourable.
- Passes stringent MMS oil/grease regulations for discharge offshore of < 29ppm
- Formulated with the highest quality ingredients, 42% by wt, dry polymer per pail

Application

RigXan-L plus tm is compatible with typically used completion, drilling and stimulation fluids. The product mixes easily in fresh water and a variety of brines. For an application rate specific to your requirements please contact the Rig-Chem, Inc. sales and technical support staff.

Handling

Improper handling of this product can be injurious to workers. Observe all safety precautions shown on the label and in the Material Safety Data Sheet.